

SAAK Pool Grout

Swimming Pool Tile Grout



DESCRIPTION :

SAAK POOL GROUT is a polymer modified cement based powder it for the use filing the joints of ceramic tile marble & Mosaic stones on smooth and coarse surface, It is available in white, grey and all type of colours, SAAK POOL GROUT is suitable for internal and external applications.

ADVANTAGE :

- Good performance properties.
- Low shrinkage.
- Water & Weather resistance (suitable for swimming pools).
- For interior & exterior usage.
- Available in a range of attractive colours.

USES:

Suitable for grouting joints of ceramic tiles, marble, and mosaic on both smooth and rough surfaces. Ideal for use in kitchens, bathrooms, swimming pools, shower areas, façades, terraces, and other internal and external tile applications.

TECHNICAL DATA :

These application values are measured in the standard conditions of +23C and 50% R.H.

Color	White, grey and riety of standard color
Application Temperatu	23 ± 2°C, Relative Humidity: 50 ± 5%
Amount of water used for preparing the grout	Approx.33%
Coverage	4kg/1sqm (5mm thickness)
Abrasion Resistance	472 mm ³ EN 13888 – 2 Clause 9
Flexural Strength	7.5 N/mm ² EN 13888-2 Clause 9.1
Compressive Strength	30 N/mm ² EN 13888-2 Clause 9.1
Water Absorption	4.48 g after 30 min, 9.88 g after 240 min EN13888-2: 2022-11/9.2

INSTRUCTIONS FOR USE

Ensure all tiles are firmly fixed in position and fully cured before applying Saak Pool Grout. Clean the joints thoroughly to remove any dust, debris, or adhesive residue. The tile joint width should not exceed 4 mm for standard applications. Grouting should commence only after adhesive drying and substrate stabilization are confirmed.

SURFACES :

Saak Pool Grout is suitable for smooth and coarse surfaces. It can be used for internal and external applications on ceramic tiles, marble, and mosaic. Ensure the surface is clean, dry, and free from oil, dust, and loose particles. Grouting should start only after all movement or shrinkage in the substrate has ceased to ensure proper adhesion and durability.

MIXING :

Mix 3.6 litres of clean water with each 10 kg bag of Saak Pool Grout. Use a slow-speed drill fitted with a suitable paddle for best results. Gradually add the powder into the water and mix continuously until a smooth, lump-free, creamy paste is formed. Let the mixture stand for 10 minutes before use to allow full hydration.

APPLICATION :

Apply Saak Pool Grout to the joints between ceramic tiles, marble, or mosaic using a rubber float, sponge, or soft cloth. Firmly press the grout into the joints and spread evenly across the surface. Remove excess material from the tile surface using a damp cloth or sponge while the grout is still fresh.

For profiling, run a gloved finger or rounded tool along the joints to achieve a smooth finish. Once dry, clean the tile surface thoroughly with a damp sponge to remove any remaining haze. For textured tiles, always clean uncured grout immediately before it hardens, as delayed removal may result in permanent residue.



SAAK Pool Grout

Swimming Pool Tile Grout

CLEANING :

Saak Pool Grout should be cleaned from tools and equipment immediately after use with clean water. Once cured, the grout can only be removed mechanically.

JOINTS :

Ensure tile joints are clean, dry, and free from adhesive residue, dust, or moisture before grouting. A minimum joint width of 2 mm is recommended for standard tiles. Grouting should be performed after the tile adhesive has fully cured and all movement or shrinkage in the substrate has stopped.

YIELD :

A 10 kg bag of Saak Pool Grout covers approximately 50 m² at a 2 mm joint width, depending on tile size, joint depth, and surface condition.

FINISHING :

After applying the grout, clean off excess material using a damp sponge before it starts to harden. Once partially set, wipe the tile surface again to remove any haze. Allow grout to cure for at least 24 hours before exposing the area to water or foot traffic.

PACKAGING :

Saak Pool Grout is available in 10 kg bags. Custom color options available upon request.

STORAGE :

Unopened bags of Saak Pool Grout have a shelf life of 12 months when stored in a dry, shaded area at temperatures between 20–30°C and kept off the ground.

HEALTH AND SAFETY :

Saak Pool Grout is a cement-based, polymer-modified material. Use protective gloves, dust masks, and eye protection when handling. Avoid inhalation of dust or contact with eyes. Refer to the Safety Data Sheet (SDS) for complete safety guidance.

SAAK also provides various technical information such as CAD details, detailed method statements, specification clauses, application manuals, product selectors and technical support both in contractors and consultants offices as well as construction sites. For further information on these products and systems kindly check our website or contact your local SAAK representative.

